



PRODUCTIVE.



RELIABLE.



AFFORDABLE.

DATA I/O CORPORATION



Redmond, WA



www.dataio.com



info@dataio.com



+1 800-3-DATAIO



PSV3000-W

The PSV3000-W is the cost-effective entry point for high-quality automated device programming for low volume applications.

Productive: *Ideal for first time automation*

AUTOMATED PROGRAMMING WITH EASY CHANGEOVER

- Up to 700 parts/hour
- Supports 2 FlashCORE III programmers (8 sockets)
- Supports 1 LumenX programmer (8 sockets)

FLEXIBLE OPTIONS

- Integrated media options
- Fiber laser & ink dot marking
- Parts down to 4mm x 4mm
- Large parts up to 42.5 mm x 42.5mm

OPTIMIZED ALGORITHMS & UNIVERSAL DEVICE SUPPORT

- Universal device support on FlashCORE III
- Ultra-fast programming for eMMC and UFS on LumenX

Reliable: *Engineered for highest quality programming, uptime, & production yield*

HIGHEST QUALITY PROGRAMMING RESULTS

- HIC adapters for highest programming yield
- Value added software

INTELLIGENT SYSTEM DESIGN & INTEGRATION

- Proven pick & place head, programming engine & handling software

INTEGRATED VISION SYSTEM FOR PRECISE PLACEMENT

- +/- 30 micron for repeatable precision placement

Affordable: *high quality automated programming for the lowest cost per device*

LOWEST TOTAL COST

- Significantly reduce labor cost
- Save up to 3x cost per programmed part

INVESTMENT PROTECTION

- Works with existing FlashCORE & LumenX adapters & algorithms
- Growing support for LumenX ensures your investment is protected now and in the future

GLOBAL SERVICE & SUPPORT

- Local service, engineering & support
- Regional spare parts

DEVICE HANDLING SYSTEM

- | | | | |
|---------------------------------|---|-------------------------------|---|
| • Throughput: | Handler rated up to 700 devices per hour | • System Software: | TaskLink for Windows, CH700, Windows 10 |
| • Placement Accuracy: | ± .02mm | • Frame Dimensions: | 1290mm D x 870mm W x 1520mm H (not including media I/O) |
| • Pick-and-Place Method: | Single-probe stepper actuated z-motion with servo-drive theta (rotation axis) | • Shipping Dimensions: | 1310mm D x 930mm W x 1760mm H (not including media I/O) |
| • Probe Stroke: | 50mm (max) | • Net Weight: | 450kg (992 lbs) |
| • Alignment: | Upward looking camera | • Shipping Weight: | 550kg (1212 lbs) |
| • Regulatory Compliance: | CE Compliant, RoHS, WEEE | | |

I/O MEDIA OPTIONS

Any combination of input/output media I/O

- **Tape Input:** 8mm - 56mm
- **Tape Output:** 8mm - 44mm (adjustable)
- **Tray Feeder Input/Output:** Supports up to 20 JEDEC Trays
- **Manual Tray:** Available without any special tooling
- **Tube Input/Output**
- **Reject Bin**

VALUE ADDED SOFTWARE

- **Automotive Performance PAK**
- **NAND Flash Bad Block Management**
- **Command Line Interface (LumenX)**
- **ConneX® Software**

DEVICE MARKING OPTION

- **Laser Marker:** Fiber laser marking
- **Power:** 0 - 10 Watts
- **Ink Dot Marking** Marks parts as small as 4mm x 4mm

ADDITIONAL OPTIONS

- **2D Tape-out Inspection**
- **Integrated Ionizers**
- **Barcode Scanner**

PROGRAMMING ENGINE, ADAPTERS & DEVICE SUPPORT

Programmer:

- **FlashCORE III**
- **LumenX with TurboBoost**

Socketing Technology:

- **Standard burn-in sockets** (typically 5,000 - 10,000 insertions per socket)
- **High Insertion Count Sockets** (HIC) for BGA, TSOP, QFP (typically 250,000 insertions per socket)

Package Support:

PLCC, SOIC, SON, WSON, SSOP, CSP, BGA, uBGA and FPGA, QFP, TQFP, TSOP, PoP, DIP and more

Universal Device Support:

- **FlashCORE III:** Flash Memory (NOR, NAND, MCP, MMC, eMMC, SD, MoviNAND, OneNAND, iNAND, Serial Flash, EEPROM, EPROM and more), Microcontrollers and Logic devices (CPLD, FPGA's, PLD's) and more
- **LumenX:** eMMC, UFS, SD, SPI NOR, Microcontrollers with support for additional device technologies in process

Device Programming & Testing:

Program, continuity, checksum, blank check, mis-insertion, test, verify, backwards device, two pass verify, ID check, Illegal bit-check

SUPPORT OPTIONS & SERVICE

- **PSV3000 Basic Spares Kit**
- **PSV3000 Supplemental Spares Kit**
- **PSV LumenX Spares Kit**
- **Operator Training**
- **Extended Service Contracts:**

The first year of support is included in the system purchase price and can be extended via extended service support renewal. Data I/O offers a suite of options to cover both hardware and system software (consumables are not included).

REQUIREMENTS

- **Input Voltage:** 208-240 VAC, 50/60 Hz, Single-phase 10 Amps Max
- **Operating Temperature:** 55°F to 86°F (+13°C to + 30°C)
- **Humidity:** 35% to 90% RH Non-Condensing
- **Air Pressure:** 80psi (5.5 bar)
- **Air Flow:** 6 SCFM (max)

Americas
Data I/O Corporation
Redmond, Washington, USA
Website: www.dataio.com
Email: sales@dataio.com

Europe
Data I/O GmbH
Gräfelfing, Germany
Website: www.dataio.de
Email: salesgmbh@data-io.de

Asia
Data I/O Electronics (Shanghai) Co. Ltd
Shanghai, China, PRC
Website: www.dataio.cn
Email: ChinaSales@dataio.cn

